

SY-JZ

flexible, number coded, with steel wire braiding, meter marking



Technical data

- PVC cable adapted to
DIN VDE 0285-525-2-51 /
DIN EN 50525-2-51
- **Temperature range**
flexing -15°C to +80°C
fixed installation -40°C to +80°C
- **Nominal voltage**
U₀/U 300/500 V
- **Test voltage**
4000 V
- **Breakdown voltage**
min. 8000 V
- **Minimum bending radius**
flexing 20x cable Ø
fixed installation 6x cable Ø

Cable structure

- Bare copper conductor, fine wire
acc. to DIN VDE 0295 cl.5 /
IEC 60228 cl.5
- Core insulation of PVC
compound type Z 7225
- Core identification to DIN VDE 0293
black cores with continuous white
numbering
- GN-YE conductor, 3 cores and above
in the outer layer
- Cores stranded in layers with
optimal lay length
- Inner sheath of PVC
- Galvanized steel wire braid
- Outer sheath of PVC
- Sheath colour: transparent
- With meter marking

Properties

- Extensively oil resistant,
oil-/chemical resistance
see "Technical Information"
- The materials used during manufacturing
are cadmium-free, contain no silicone
and are free from substances harmful
to the wetting properties of lacquers

Tests

- Flame retardant acc. to
DIN VDE 0482-332-1-2 /
DIN EN 60332-1-2 / IEC 60332-1-2

Note

- G = with GN-YE conductor
x = without GN-YE conductor (OZ)
- Cleanroom qualification tested with analog
type. Please note "cleanroom qualified"
when ordering.
- AWG sizes are approximate equivalent
values. The actual cross section is in mm².
- Screened analogue type:
SY-JB

Application

SY-JZ cables are used as connecting and control cables in tool machinery, plant installation, power stations and in data equipment. The braided screen offers best possible protection against mechanical damage. The galvanized coating on the steel wire braiding not only helps protect against corrosion, but also notably improves the soldering performance.

The clear transparent outer sheath gives the cable in addition an optical reevaluation.

CE = Product conforms with Low-Voltage Directive 2014/35/EU.

Part no.	No. cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
12001	2 x 0,5	7,4	9,6	80,0	20
12002	3 G 0,5	7,7	14,4	92,0	20
12003	4 G 0,5	8,1	19,2	102,0	20
12004	5 G 0,5	9,0	24,0	119,0	20
12005	7 G 0,5	9,5	33,6	157,0	20
12006	10 G 0,5	11,4	48,0	205,0	20
12007	12 G 0,5	11,9	58,0	218,0	20
12008	14 G 0,5	12,5	67,0	242,0	20
12009	18 G 0,5	13,7	86,0	340,0	20
12010	21 G 0,5	14,3	101,0	370,0	20
12114	25 G 0,5	15,8	120,0	406,0	20
12012	30 G 0,5	16,7	144,0	439,0	20
12013	35 G 0,5	17,9	168,0	500,0	20
12014	40 G 0,5	18,5	192,0	565,0	20
12015	42 G 0,5	19,4	202,0	593,0	20
12016	50 G 0,5	20,9	240,0	690,0	20
12017	61 G 0,5	22,1	293,0	843,0	20
12018	80 G 0,5	25,4	384,0	1050,0	20
12011	100 G 0,5	28,1	480,0	1240,0	20

Part no.	No. cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
12019	2 x 0,75	7,9	14,4	98,0	19
12020	3 G 0,75	8,2	21,6	103,0	19
12021	4 G 0,75	9,1	28,8	122,0	19
12022	5 G 0,75	9,7	36,0	142,0	19
12112	6 G 0,75	10,5	43,2	180,0	19
12023	7 G 0,75	10,5	50,0	185,0	19
12188	8 G 0,75	11,1	57,6	201,0	19
12024	9 G 0,75	12,1	65,0	249,0	19
12113	10 G 0,75	12,8	72,0	252,0	19
12025	12 G 0,75	13,4	86,0	292,0	19
12026	15 G 0,75	14,4	108,0	335,0	19
12027	18 G 0,75	15,2	130,0	388,0	19
12028	21 G 0,75	16,2	151,0	474,0	19
12029	25 G 0,75	17,7	180,0	503,0	19
12030	32 G 0,75	19,5	230,0	644,0	19
12031	34 G 0,75	20,1	245,0	663,0	19
12032	41 G 0,75	21,5	296,0	741,0	19
12033	50 G 0,75	23,6	360,0	925,0	19
12034	61 G 0,75	25,0	439,0	1082,0	19

Continuation ►

SY-JZ

flexible, number coded, with steel wire braiding, meter marking



Part no.	No. cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
12035	2 x 1	8,2	19,2	112,0	18
12036	3 G 1	9,0	28,8	132,0	18
12037	4 G 1	9,5	38,4	143,0	18
12038	5 G 1	10,1	48,0	166,0	18
12039	6 G 1	10,9	58,0	22,0	18
12040	7 G 1	10,9	67,0	227,0	18
12041	8 G 1	12,0	77,0	277,0	18
12042	9 G 1	12,8	86,0	295,0	18
12043	12 G 1	14,0	115,0	340,0	18
12044	14 G 1	14,7	134,0	420,0	18
12045	18 G 1	16,3	173,0	500,0	18
12046	20 G 1	17,0	192,0	532,0	18
12047	25 G 1	18,6	240,0	664,0	18
12048	34 G 1	21,3	326,0	845,0	18
12049	36 G 1	21,3	346,0	857,0	18
12050	41 G 1	23,0	394,0	993,0	18
12051	50 G 1	25,3	480,0	1112,0	18
12052	56 G 1	25,9	538,0	1225,0	18
12053	61 G 1	26,9	586,0	1306,0	18
12054	65 G 1	27,8	624,0	1504,0	18
12055	80 G 1	30,7	768,0	1750,0	18
12056	100 G 1	33,9	960,0	1950,0	18
12057	2 x 1,5	9,2	29,0	129,0	16
12058	3 G 1,5	9,6	43,0	149,0	16
12059	4 G 1,5	10,4	58,0	185,0	16
12060	5 G 1,5	11,1	72,0	205,0	16
12109	6 G 1,5	12,2	87,0	255,0	16
12061	7 G 1,5	12,2	101,0	285,0	16
12062	8 G 1,5	13,2	115,0	340,0	16
12063	9 G 1,5	14,1	130,0	347,0	16
12064	10 G 1,5	15,0	144,0	418,0	16
12065	11 G 1,5	15,0	158,0	430,0	16
12066	12 G 1,5	15,4	173,0	444,0	16
12067	14 G 1,5	16,4	202,0	533,0	16
12068	18 G 1,5	18,0	259,0	593,0	16
12069	25 G 1,5	21,0	360,0	781,0	16
12070	32 G 1,5	23,1	461,0	1015,0	16
12071	34 G 1,5	24,0	490,0	1124,0	16
12072	42 G 1,5	25,9	605,0	1401,0	16
12073	50 G 1,5	28,4	720,0	1583,0	16
12074	61 G 1,5	30,2	878,0	1810,0	16
12075	80 G 1,5	34,4	1152,0	2316,0	16
12076	100 G 1,5	38,4	1440,0	2900,0	16

Part no.	No. cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
12077	2 x 2,5	10,6	48,0	185,0	14
12078	3 G 2,5	11,1	72,0	248,0	14
12079	4 G 2,5	12,2	96,0	290,0	14
12080	5 G 2,5	13,3	120,0	347,0	14
12081	7 G 2,5	14,2	168,0	420,0	14
12082	12 G 2,5	18,5	288,0	660,0	14
12083	14 G 2,5	19,7	336,0	750,0	14
12084	18 G 2,5	21,6	432,0	893,0	14
12085	20 G 2,5	23,0	480,0	1169,0	14
12086	25 G 2,5	25,6	600,0	1458,0	14
12087	30 G 2,5	27,3	720,0	1686,0	14
12088	34 G 2,5	29,4	816,0	1869,0	14
12089	50 G 2,5	34,7	1200,0	2200,0	14
12090	61 G 2,5	36,8	1464,0	3000,0	14
12115	3 G 4	12,6	117,0	350,0	12
12091	4 G 4	13,9	154,0	428,0	12
12092	5 G 4	15,2	192,0	504,0	12
12093	7 G 4	16,6	269,0	640,0	12
12094	11 G 4	21,0	422,0	1204,0	12
12095	4 G 6	16,4	230,0	571,0	10
12096	5 G 6	17,9	288,0	671,0	10
12097	7 G 6	19,6	403,0	845,0	10
12098	4 G 10	19,9	384,0	943,0	8
12099	5 G 10	22,0	480,0	1065,0	8
12100	7 G 10	24,0	672,0	1551,0	8
12101	4 G 16	24,1	614,0	1360,0	6
12102	5 G 16	26,7	768,0	1740,0	6
12103	7 G 16	29,2	1075,0	2166,0	6
12104	4 G 25	29,1	960,0	2020,0	4
12105	5 G 25	32,2	1200,0	2465,0	4
12106	4 G 35	32,1	1344,0	2570,0	2
12107	5 G 35	35,5	1680,0	3185,0	2
12108	4 G 50	37,9	1920,0	3513,0	1
12116	5 G 50	42,0	2400,0	4248,0	1
12111	4 G 70	43,0	2688,0	4810,0	2/0
12117	5 G 70	47,8	3360,0	5880,0	2/0
12110	4 G 95	49,6	3648,0	6360,0	3/0
12118	5 G 95	54,8	4560,0	8071,0	3/0
12119	4 G 120	54,6	4608,0	8170,0	4/0
12327	4 G 150	59,8	5760,0	9970,0	300 kcmil

Dimensions and specifications may be changed without prior notice. (RA01)