


Referenčné normy: EN 50085-1, EN 50085-2-3

ÚLOŽNÉ KANÁLY - PERFOROVANÉ

Dodávané s krytom
 Farba: sivá RAL 7030
 Dĺžka kanála 2 m
 Prevádzková teplota: -15 °C do +60 °C



Rozmery š x v	Výška štrbiny	Farba	Balenie	Katalógové číslo	
				štand. perforácia	zhustená perforácia
25x30	17,5	■	58	874.2530	874.R2530
25x40	27,5	■	48	874.2540	874.R2540
25x60	46	■	34	874.2560	874.R2560
25x80	66	■	28	874.2580	874.R2580
40x30	17,5	■	38	874.4030	874.R4030
40x40	27,5	■	30	874.4040	874.R4040
40x60	46	■	22	874.4060	874.R4060
40x80	66	■	36	874.4080	874.R4080
60x40	27,5	■	40	874.6040	874.R6040
60x60	46	■	32	874.6060	874.R6060
60x80	66	■	24	874.6080	874.R6080
80x40	27,5	■	32	874.8040	874.R8040
80x60	46	■	24	874.8060	874.R8060
80x80	66	■	16	874.8080	874.R8080
100x40	27,5	■	24	874.0040	874.R0040
100x60	46	■	20	874.0060	874.R0060
100x80	66	■	16	874.0080	874.R0080
120x40	27,5	■	20	874.0240	874.R0240
120x60	46	■	14	874.0260	874.R0260
120x80	66	■	12	874.0280	874.R0280

VIAZACIE ŠPIRÁLY**Zväzkovacie špirály káblov - plastové**

Vnútorý Ø	Vonkajší Ø	Farba	Balenie	Katalógové číslo
3	5	■	25/700	865.603
4	6	■	25/600	865.604
6	8	■	25/500	865.606
8	10	■	25/400	865.608
10	12	■	25/200	865.610
12	14	■	20/160	865.612
14	16	■	20/120	865.614

Referenčné normy: EN 50146

VIAZACIE PÁSKY

Materiál: PA6.6, odolný UV žiareniu (len v čiernom prevedení)
 150 hod. QUV-B-ISO4892
 Teplota použitia: -40 °C až +85 °C
 Glow wire test: 650 °C, UL 94 V2
 Halogén free



Rozmer (mm)	Rozsah zväzku Ø mm	Pevnosť kg	Balenie	Katalógové číslo	
				farba	*
2,4x75	0,75-15	6,12	100/20 000	839.42080	839.52080
2,5x95	1-21	8,16	100/15 000	839.42100	839.52100
2,5x135	1-32	8,16	100/12 000	839.42120	839.52120
2,6x160	1-40	8,16	100/10 000	839.42160	839.52160
2,6x200	1-50	8,16	100/8000	839.42200	839.52200
3,6x140	2-35	13,26	100/7000	839.43140	839.53140
3,6x200	2-50	13,26	100/7000	839.43200	839.53200
3,6x290	2-80	13,26	100/4500	839.43300	839.53300
3,6x370	2-103	13,26	100/4000	839.43370	839.53370
4,8x180	2-45	22,44	100/5000	839.44190	839.54190
4,8x200	3-50	22,44	100/4000	839.44200	839.54200
4,8x250	3-68	22,44	100/4500	839.44250	839.54250
4,8x290	3,5-79	22,44	100/3500	839.44300	839.54300
4,8x360	3,5-103	22,44	100/3000	839.44370	839.54370
4,8x430	3,5-115	22,44	100/5000	839.44430	839.54430
7,8x180	3,5-45	55,8	100/2500	839.47200	839.57200
7,8x300	4-80	55,8	100/1500	839.47290	839.57290
7,8x365	8-100	55,8	100/1500	839.47370	839.57370
9x780	32-233	71,4	100/1300	839.47780	839.57780
9x1220	375	80,0	100	-	839.571220
12,5x1000	302	110,0	50/1000	839.481000	839.581000

* odolný UV žiareniu (len v čiernom prevedení) 150 hod. QUV-B-ISO4892

VIAZACIE PÁSKY

Materiál: PA12, odolný UV žiareniu 600 hod. QUV-B-ISO4892
 Teplota použitia: -40 °C až +85 °C
 Glow wire test: 650 °C, UL 94 V2
 Halogén free



Rozmer (mm)	Rozsah zväzku Ø mm	Pevnosť kg	Balenie	Farba	Katalógové číslo
6x115	4-25	25	100/2000	■	839.39/6115
6x175	10-45	28	100/2000	■	839.39/6175
9x120	4-22	48	100/2000	■	839.39/9120
9x180	10-42	48	100/2000	■	839.39/9180
9x265	30-60	51	100/2000	■	839.39/9260
9x360	30-93	51	100/2000	■	839.39/9350

