



### Main

Range name	Sedna
Function	Socket-outlet
Delivery form	Without frame
Outlet poles configuration	2P + E with shutters
Outlet standard description	Pin earth
Rated current	16 A at 250 V AC

### Complementary

Power range	3680 W
Kind of terminals	Lift terminals
Terminal capacity	2 cable(s) 2.5 mm <sup>2</sup>
Wire structure	Rigid Flexible
Wire stripping length	13 mm
Material of visible parts	ASA + PC
Surface finish	Glossy
Fixing mode	Claws, span of claws working range: 52...69 mm Screws
Height	71 mm
Width	71 mm
Depth	38.3 mm
Depth of visual part	10 mm
Net weight	0.069265 kg

### Environment

Standards	IEC 60884-1
-----------	-------------

Product certifications	B
IP degree of protection	IP20

### Packing Units

Package 1 Weight	68 g
Package 2 Weight	764.67 g
Package 3 Weight	9.853 kg

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### Contractual warranty

Warranty	18 months
----------	-----------