

Séria OPTIMA

Referenčné normy: EN 60309-1, EN 60309-2

ZÁSUVKY SPOJOVACIE - IP44 pre atypické použitie

Farba: čierna



Priame						
	Popis	Farba	Balenie	Katalógové číslo		
16A	2P+ E 6h 50/60 Hz 200-250V	■	10/50	313.1643.K		
	3P+ E 6h 50/60 Hz 380-415V	■	10/50	313.1646.K		
	3P+N+E 6h 50/60 Hz 380-415V	■	10/50	313.1647.K		
32A	2P+ E 6h 50/60 Hz 200-250V	■	10/40	313.3243.K		
	3P+ E 6h 50/60 Hz 380-415V	■	10/40	313.3246.K		
	3P+N+E 6h 50/60 Hz 380-415V	■	10/40	313.3247.K		

ZÁSUVKY SPOJOVACIE - IP67 pre atypické použitie

Farba: čierna



Priame						
	Popis	Farba	Balenie	Katalógové číslo		
16A	2P+ E 6h 50/60 Hz 200-250V	■	10/40	318.1643.K		
	3P+ E 6h 50/60 Hz 380-415V	■	10/40	318.1646.K		
	3P+N+E 6h 50/60 Hz 380-415V	■	10/40	318.1647.K		
32A	2P+ E 6h 50/60 Hz 200-250V	■	10/40	318.3243.K		
	3P+ E 6h 50/60 Hz 380-415V	■	10/40	318.3246.K		
	3P+N+E 6h 50/60 Hz 380-415V	■	10/40	318.3247.K		

Séria EUREKA - MIL

Referenčné normy: EN 60309-1, EN 60309-2

ZÁSUVKY SPOJOVACIE - IP67 pre vojenské aplikácie

Farba: zelená



Priame						
	Popis	Farba	Balenie	Katalógové číslo		
16A	2P+ E 6h 50/60 Hz 200-250V	■	10/40	316.81643		
	3P+ E 6h 50/60 Hz 380-415V	■	10/40	316.81646		
	3P+N+E 6h 50/60 Hz 380-415V	■	10/40	316.81647		
32A	2P+ E 6h 50/60 Hz 200-250V	■	10/40	316.83243		
	3P+ E 6h 50/60 Hz 380-415V	■	10/40	316.83246		
	3P+N+E 6h 50/60 Hz 380-415V	■	10/40	316.83247		
63A	2P+E 6h 50/60 Hz 200-250V	■	1/1	315.86343		
	3P+E 6h 50/60 Hz 380-415V	■	1/1	315.86346		
	3P+N+E 6h 50/60 Hz 380-415V	■	1/1	315.86347		
125A	2P+E 6h 50/60 Hz 200-250V	■	1/1	315.812543		
	3P+E 6h 50/60 Hz 380-415V	■	1/1	315.812546		
	3P+N+E 6h 50/60 Hz 380-415V	■	1/1	315.812547		

Séria OPTIMA

Referenčné normy: EN 60309-1, EN 60309-2

ZÁSUVKY - VSTAVNÉ - IP44

Rozmer príruby: 70x87 mm (16A)
84x106 mm (32A)



Šikmé						
	Popis	Farba	Balenie	Katalógové číslo		
16A	2P+ E 6h 50/60 Hz 200-250V	■	10/100	413.1663		
	3P+ E 6h 50/60 Hz 380-415V	■	10/100	413.1666		
	3P+N+E 6h 50/60 Hz 380-415V	■	10/100	413.1667		
32A	2P+ E 6h 50/60 Hz 200-250V	■	10/50	413.3263		
	3P+ E 6h 50/60 Hz 380-415V	■	10/50	413.3266		
	3P+N+E 6h 50/60 Hz 380-415V	■	10/50	413.3267		

Šikmé bezskrútkové svorky						
	Popis	Farba	Balenie	Katalógové číslo		
16A	2P+ E 6h 50/60 Hz 200-250V	■	10/100	413.1663F		
	3P+ E 6h 50/60 Hz 380-415V	■	10/100	413.1666F		
	3P+N+E 6h 50/60 Hz 380-415V	■	10/100	413.1667F		
32A	2P+ E 6h 50/60 Hz 200-250V	■	10/50	413.3263F		
	3P+ E 6h 50/60 Hz 380-415V	■	10/50	413.3266F		
	3P+N+E 6h 50/60 Hz 380-415V	■	10/50	413.3267F		

ZÁSUVKY - VSTAVNÉ - IP67

Rozmer príruby: 70x87 mm (16A)
84x106 mm (32A)



Šikmé						
	Popis	Farba	Balenie	Katalógové číslo		
16A	2P+ E 6h 50/60 Hz 200-250V	■	10/100	418.1663		
	3P+ E 6h 50/60 Hz 380-415V	■	10/100	418.1666		
	3P+N+E 6h 50/60 Hz 380-415V	■	10/100	418.1667		
32A	2P+ E 6h 50/60 Hz 200-250V	■	10/50	418.3263		
	3P+ E 6h 50/60 Hz 380-415V	■	10/50	418.3266		
	3P+N+E 6h 50/60 Hz 380-415V	■	10/50	418.3267		

Šikmé bezskrútkové svorky						
	Popis	Farba	Balenie	Katalógové číslo		
16A	2P+ E 6h 50/60 Hz 200-250V	■	10/100	418.1663F		
	3P+ E 6h 50/60 Hz 380-415V	■	10/100	418.1666F		
	3P+N+E 6h 50/60 Hz 380-415V	■	10/100	418.1667F		
32A	2P+ E 6h 50/60 Hz 200-250V	■	10/50	418.3263F		
	3P+ E 6h 50/60 Hz 380-415V	■	10/50	418.3266F		
	3P+N+E 6h 50/60 Hz 380-415V	■	10/50	418.3267F		

