


dle DIN 46228

pro Cu laněné vodiče (nelze použít pro plné vodiče!)

Materiál:

dutinka - měď, galvanicky pocínovaná
izolace - polyamid nebo polypropylen

Teplotní stálost: -20°C až +105°C



Označení	Průřez vodiče v mm ²	Barevný kód			Rozměry v mm					
		I	II	III	l ₁	l ₂	d ₁	d ₂	s ₁	s ₂
DI 0,14-6	0,14	●	●	-	10,4	6,0	0,70	1,6	0,12	0,20
DI 0,25-6	0,25	●	●	-	10,5	6,0	0,75	2,0	0,25	0,25
DI 0,25-8		●	●	-	12,5	8,0	0,75	2,0	0,25	0,25
DI 0,34-6	0,34	●	●	-	10,5	6,0	0,75	2,0	0,25	0,25
DI 0,34-8		●	●	-	12,5	8,0	0,75	2,0	0,25	0,25
DI 0,5-6	0,50	○	●	○	12,0	6,0	1,00	2,6	0,15	0,25
DI 0,5-8		○	●	○	14,0	8,0	1,00	2,6	0,15	0,25
DI 0,5-10		○	●	○	16,0	10,0	1,00	2,6	0,15	0,25
DI 0,75-6	0,75	●	○	●	12,0	6,0	1,2	2,8	0,15	0,25
DI 0,75-8		●	○	●	14,0	8,0	1,2	2,8	0,15	0,25
DI 0,75-10		●	○	●	16,0	10,0	1,2	2,8	0,15	0,25
DI 0,75-12		●	○	●	18,0	12,0	1,2	2,8	0,15	0,25
DI 1,0-6	1,0	●	●	●	12,0	6,0	1,4	3,0	0,15	0,25
DI 1,0-8		●	●	●	14,0	8,0	1,4	3,0	0,15	0,25
DI 1,0-10		●	●	●	16,0	10,0	1,4	3,0	0,15	0,25
DI 1,0-12		●	●	●	18,0	12,0	1,4	3,0	0,15	0,25
DI 1,5-6	1,5	●	●	●	12,0	6,0	1,7	3,5	0,15	0,25
DI 1,5-8		●	●	●	14,0	8,0	1,7	3,5	0,15	0,25
DI 1,5-10		●	●	●	16,0	10,0	1,7	3,5	0,15	0,25
DI 1,5-12		●	●	●	18,0	12,0	1,7	3,5	0,15	0,25
DI 1,5-18		●	●	●	24,0	18,0	1,7	3,5	0,15	0,25
DI 2,5-8	2,5	●	●	●	14,0	8,0	2,2	4,2	0,15	0,25
DI 2,5-12		●	●	●	18,0	12,0	2,2	4,2	0,15	0,25
DI 2,5-18		●	●	●	24,0	18,0	2,2	4,2	0,15	0,25

Doplňující údaje:

- standardní barevný kód pro GPH je II.
- lisovací nářadí viz. kap. 9


dle DIN 46228

pro Cu laněné vodiče (nelze použít pro plné vodiče!)

Materiál:

dutinka - měď, galvanicky pocínovaná
izolace - polyamid nebo polypropylen

Teplotní stálost: -20°C až +105°C



Označení	Průřez vodiče v mm ²	Barevný kód			Rozměry v mm					
		I	II	III	l ₁	l ₂	d ₁	d ₂	s ₁	s ₂
DI 4-10	4	●	●	●	17,0	10,0	2,8	4,8	0,20	0,30
DI 4-12		●	●	●	20,0	12,0	2,8	4,8	0,20	0,30
DI 4-18		●	●	●	26,0	18,0	2,8	4,8	0,20	0,30
DI 6-12	6	●	●	●	20,0	12,0	3,5	6,3	0,20	0,30
DI 6-18		●	●	●	26,0	18,0	3,5	6,3	0,20	0,30
DI 10-12	10	●	●	●	22,0	12,0	4,5	7,6	0,20	0,40
DI 10-18		●	●	●	28,0	18,0	4,5	7,6	0,20	0,40
DI 16-12	16	○	●	●	24,0	12,0	5,8	8,8	0,20	0,40
DI 16-18		○	●	●	28,0	18,0	5,8	8,8	0,20	0,40
DI 25-16	25	●	●	●	29,0	16,0	7,3	11,2	0,20	0,40
DI 25-22		●	●	●	36,0	22,0	7,3	11,2	0,20	0,40
DI 35-16	35	●	●	●	30,0	16,0	8,3	12,7	0,20	0,40
DI 35-25		●	●	●	39,0	25,0	8,3	12,7	0,20	0,40
DI 50-20	50	●	●	●	36,0	20,0	10,3	15,0	0,30	0,50
DI 50-25		●	●	●	40,0	25,0	10,3	15,0	0,30	0,50
DI 70-20	70	●	●	-	37,0	20,0	12,5	16,0	0,40	0,60
DI 95-25	95	●	●	-	44,0	25,0	14,5	18,0	0,40	0,60
DI 120-27	120	●	●	-	48,0	27,0	16,5	21,0	0,50	0,70
DI 150-32	150	●	●	-	58,0	32,0	19,3	23,0	0,50	1,00

Doplňující údaje:

- standardní barevný kód pro GPH je II.
- lisovací nářadí viz. kap. 9, 10