



### Main

Range of product	Lighting and power sockets
Accessory / separate part category	Lighting accessory
Product or component type	Lamp
Device application	Multi-purpose
Device composition	1 lamp 1 cable 1 fixed base
Power factor	0.9

### Complementary

Outlet standard	Without socket
Rated lamp wattage	10 W
[Ue] rated operational voltage	120 V AC 50/60 Hz
Bulb base	E27
Bulb type	LED
Control type	Built-in recessed switch
Luminous flux	1100 lm
Colour temperature	4000 K
Service life in hours	25000 h
Electrical connection	Cable 3 m supplied
Fixing mode	Screws Adhesive
Range compatibility	Spacial Thalassa
Material	PC (UL94 V-0)
Height	403.5 mm
Width	91.5 mm
Depth	66 mm
Colour	Black (RAL 9005)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environment

IP degree of protection	IP20 conforming to IEC 60529
Electrical insulation class	Class II
Standards	IEC 60598 UL 94
Ambient air temperature for operation	-16...65 °C
Ambient air temperature for storage	-10...60 °C

## Packing Units

Package 1 Weight	0.882 kg
------------------	----------

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------