



Wireless Shading, package, pre-programmed

Part no. CPAD-00/214
Catalog No. 193729

EL-Nummer (Norway) 4560762

Delivery program

| | | | |
|--------------------------|--|--|--|
| Product Type | | | Packaged Units Actuator Pushbutton |
| Mounting type | | | Flush mounted Surface mounted |
| Power supply | | | Battery Mains |
| Actuation Function | | | Shading |
| Pushbutton compatibility | | | 55 mm (Universal) |
| Rocker Pitch | | | 1-gang |
| Color | | | Pure White |

Technical data ETIM 7.0

| | | | |
|--|--|----|-------------------------|
| Installation bus systems (EG000032) / Shutting actuator for bus system (EC001330) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Bus system / Shutting actuator for bus system (ecl@ss10.0.1-27-14-31-28 [AKE296014]) | | | |
| Bus system KNX | | | No |
| Bus system KNX radio | | | No |
| Bus system radio frequent | | | Yes |
| Bus system LON | | | No |
| Bus system Powernet | | | No |
| Other bus systems | | | Other |
| Radio frequent bidirectional | | | Yes |
| Mounting method | | | Flush mounted (plaster) |
| Width in number of modular spacings | | | 3 |
| Bus connection included | | | Yes |
| Bus module detachable | | | No |
| Local operation/hand operation | | | No |
| With LED indication | | | Yes |
| Number of inputs | | | 0 |
| Switching current (resistive) | | A | 6 |
| Max. switching power | | W | 1380 |
| Max. number of venetian-blind outputs | | | 1 |
| With switch function | | | Yes |
| Type of current | | | AC |
| Degree of protection (IP) | | | IP20 |
| Min. depth of built-in installation box | | mm | 26 |

Additional product information (links)

| | |
|-------------------------|---|
| (IL019194ZU)CPAD | |
| (IL019194ZU)CPAD | https://es-assets.eaton.com/DOCUMENTATION/AWA_INSTRUCTIONS/MA136211192_2018_01.pdf |