



Wireless Second Switch, package, pre-programmed

Part no. CPAD-00/215
Catalog No. 193730

EL-Nummer (Norway) 4560763

Delivery program

Product Type			Packaged Units Actuator Pushbutton
Mounting type			Flush mounted Surface mounted
Power supply			Battery Mains
Actuation Function			Switching
Pushbutton compatibility			55 mm (Universal)
Rocker Pitch			1-gang
Color			Pure White

Technical data ETIM 7.0

Installation bus systems (EG000032) / Switch actuator for bus system (EC001097)			
Electric engineering, automation, process control engineering / Electrical installation, device / Bus system / Switch actuator for bus system (ecl@ss10.0.1-27-14-31-25 [AKE293014])			
Bus system KNX			No
Bus system KNX radio			No
Bus system radio frequent			Yes
Bus system LON			No
Bus system Powernet			No
Other bus systems			Other
Radio frequent bidirectional			Yes
Mounting method			Flush mounted (plaster)
Width in number of modular spacings			3
Local operation/hand operation			Yes
With LED indication			Yes
Number of binary inputs			1
Max. switching power		W	2300
Output power		W	2300
Suitable for C-load			Yes
Max. number of switching contacts			1
Max. switching current		A	10
Rated current		A	10
Rated operating voltage		V	196 - 253
Different phases connectable			No
Bus connection included			Yes
Bus module detachable			No
Min. depth of built-in installation box		mm	18
Modular expandability			Yes
Degree of protection (IP)			IP20

Additional product information (links)

(IL019195ZU)CPAD	
(IL019195ZU)CPAD	https://es-assets.eaton.com/DOCUMENTATION/AWA_INSTRUCTIONS/MA136211193_2018_01.pdf