



Sada xComfort Bridge

Typ **CPAD-00/221**  
Catalog No. **300310**

**Dodavatelský program**

Typ produktu		Balené jednotky Ovládání Tlačítko
Typ montáže		Zapuštěná montáž Povrchová montáž
Napájení		Baterie Síťové napájení
Aktivační funkce		Ztlumení
Kompatibilita tlačítek		55 mm (Universal)
Rozteč vahadla		1 souprava
Barva		Čistě bílá

**Technická data podle ETIM 7.0**

Installation bus systems (EG000032) / Dimming actuator for bus system (EC001094)		
Elektrotechnika, automatizační technika a technika řízení procesu / Elektroinstalacní zařízení, přístroj / Sbernicový systém / Sbernicový systém - stmívací aktor (ecl@ss10.0.1-27-14-31-23 [AKE291015])		
Bus system KNX		No
Bus system KNX radio		No
Bus system radio frequent		Yes
Bus system LON		No
Bus system Powernet		No
Other bus systems		xComfort
Radio frequent bidirectional		Yes
Model		Dimming actuator
Mounting method		Flush mounted (plaster)
Width in number of modular spacings		3
Bus connection included		Yes
Bus module detachable		No
Substation input		No
Local operation/hand operation		No
With LED indication		Yes
Number of outputs		1
Output power	W	0 - 100
Power boost suitable		No
Type of load		Universal and LED Retrofit
Max. control current	mA	0
Voltage	V	196 - 253
Parallel-service possible		No
Frequency	Hz	50 - 50
Degree of protection (IP)		IP20
Min. depth of built-in installation box	mm	18