

New Unica - 1 French socket-outlet - 2P+E + shutters - 16A 250V - IP21 D - white

NU304918

IVI	a	ı	r	1
-----	---	---	---	---

Range	New Unica
Device application	Power supply
Product or component type	Socket-outlet
Device presentation	Mechanism
Socket number	1
Outlet poles configuration	2P + E
Outlet standard	French
Outlet standard description	Pin earth
Ground lug position	45° ground lug

Complementary	
Cover type	With shutter
Device mounting	Flush
Rated current	16 A
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50/60 Hz
Number of modules	2 modules
Fixing mode	Clip-in
Colour tint	White (RAL 9003)
Connections - terminals	Screwless terminals
Cable cross section	02.5 mm² cable(s), 2 - cable stiffness: flexible 02.5 mm² cable(s), 2 - cable stiffness: rigid
Minimum load breaking capacity	100 operations 1.25 In and 1.1 Un, cos phi = 0.6
Electrical durability	10000 cycles, cos phi = 0.8
Insulation resistance	> 5 MOhm at 500 V
Dielectric strength	2000 V
Material	PC: mechanism cover
Surface finish	Glossy

Quantity per set	Set of 1 without packaging
Standards	IEC 60884-1 NF C 61-314
Product certifications	NF
Embedding depth	28.4 mm
Depth	37.7 mm
Width	45 mm
Height	45 mm
Net weight	0.031 kg
Surface treatment	Untreated
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

Environment

Ambient air temperature for operation	-535 °C
Ambient air temperature for storage	-550 °C
IK degree of protection	IK04
IP degree of protection	IP3x
Environmental characteristic	Acetone Bleach UV resistant Petrol Oil Alcohol Window-cleaning fluid Liquid soap

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	32.0 g
Package 1 Height	4.5 cm
Package 1 width	4.5 cm
Package 1 Length	3.8 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	394.0 g
Package 2 Height	5.0 cm
Package 2 width	10.0 cm
Package 2 Length	27.0 cm
Unit Type of Package 3	P06
Number of Units in Package 3	1120
Package 3 Weight	46.724 kg

Package 3 Height	75.0 cm
Package 3 width	60.0 cm
Package 3 Length	80.0 cm
Offer Sustainability	
Sustainable offer status	Green Premium product
Cradle to Cradle	Bronze □
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins