

# Product data sheet

Specifications



## New Unica - push-button switch Light symbol 10A screwless 2modules white

NU320618L

### Main

Range of product	New Unica
Product or component type	Push-button
Device presentation	Mechanism
Technology type	Electromechanical
Switch function	+ NO push-button
Number of rocker	1
Device application	Light control
Colour tint	White (RAL 9003)
Type of packing	Flow-pack

### Complementary

Rated current	10 A
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50/60 Hz
Electrical durability	20000 cycles, cos phi = 0.6
Insulation resistance	> 5 MOhm at 500 V
Dielectric strength	2000 V
Minimum load breaking capacity	200 operations 1.25 In and 1.1 Un, cos phi = 0.3
Opening distance	> 3 mm
Actuator	Rocker
Number of modules	2 modules
Connections - terminals	Screwless terminals
Cable cross section	0...2.5 mm <sup>2</sup> rigid cable 0...2.5 mm <sup>2</sup> flexible cable
Material	Thermoplastic ABS-UV stabilised: mechanism rocker PC (polycarbonate) GF10 FR: casing CuZn37: terminals PBT (polybutylene terephthalate) GF30: release button
Marking	Light symbol
Surface finish	Glossy

<b>Fixing mode</b>	Clip-in
<b>Width</b>	45 mm
<b>Height</b>	45 mm
<b>Depth</b>	34.25 mm
<b>Embedding depth</b>	21.15 mm
<b>Net weight</b>	0.0175 kg
<b>Ambient air temperature for operation</b>	-5...40 °C
<b>Ambient air temperature for storage</b>	-5...50 °C
<b>Standards</b>	IEC 60669-1 LV directive
<b>Product certifications</b>	CE AENOR EAC NF VDE
<b>Resistance to chemical agents</b>	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

## Environment

<b>IP degree of protection</b>	IP4X
<b>IK degree of protection</b>	IK04
<b>Environmental characteristic</b>	Oil UV resistant Acetone Liquid soap Window-cleaning fluid Petrol Alcohol Bleach

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Weight</b>	19.0 g
<b>Package 1 Height</b>	3.5 cm
<b>Package 1 width</b>	4.5 cm
<b>Package 1 Length</b>	4.5 cm
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	10
<b>Package 2 Weight</b>	274.0 kg
<b>Package 2 Height</b>	8.2 cm
<b>Package 2 width</b>	17.7 cm
<b>Package 2 Length</b>	18.5 cm
<b>Unit Type of Package 3</b>	P06
<b>Number of Units in Package 3</b>	640
<b>Package 3 Weight</b>	28.9 kg

---

<b>Package 3 Height</b>	77.0 cm
<b>Package 3 width</b>	80.0 cm
<b>Package 3 Length</b>	60.0 cm

---

## Offer Sustainability

---

<b>Cradle to Cradle</b>	Bronze <a href="#">↗</a>
<b>EU RoHS Directive</b>	Under investigation
<b>WEEE</b>	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

---