

## New Unica - TV/FM - intermediate -2 m - white

NU345318

| Range                     | New Unica                             |
|---------------------------|---------------------------------------|
| Product or component type | TV/FM socket                          |
| Device application        | Media device support<br>Communication |
| Device presentation       | Mechanism                             |
| TV socket type            | Intermediate                          |
| Colour tint               | White (RAL 9003)                      |

## Complementary

| TV connector                  | Male IEC 9.52 mm   |
|-------------------------------|--|
| Radio connector               | Female IEC 9.52 mm   |
| Path attenuation              | 1.5 dB TV/VHF signal575 MHz<br>1.5 dB TV/UHF signal170862 MHz<br>3 dB R signal88110 MHz<br>2 dB IN-OUT signal47862 MHz |
| DC current flow               | No   |
| Number of modules             | 2 modules  |
| Material                      | Thermoplastic ABS-UV stabilised: central plate   |
| Surface treatment             | Untreated  |
| Surface finish                | Glossy   |
| Marking                       | With imprint   |
| Device mounting               | Flush  |
| Fixing mode                   | Clip-in  |
| Depth                         | 33 mm  |
| Width                         | 45 mm  |
| Height                        | 45 mm  |
| Embedding depth               | 33 mm  |
| Resistance to chemical agents | Resistant to alcohol (70 %)  |

Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistance to chemical agents

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

| Environment                           |          |
|---------------------------------------|----------|
| IP degree of protection               | IP20     |
| IK degree of protection               | IK01     |
| Ambient air temperature for operation | -2555 °C |
| Ambient air temperature for storage   | -2555 °C |
| Standards                             | CE       |
| Packing Units                         |          |
| Unit Type of Package 1                | PCE      |
| Number of Units in Package 1          | 1        |
|                                       |          |

| Unit Type of Package 1       | PCE      |
|------------------------------|----------|
| Number of Units in Package 1 | 1        |
| Package 1 Weight             | 83.7 g   |
| Package 1 Height             | 3.3 cm   |
| Package 1 width              | 4.5 cm   |
| Package 1 Length             | 4.5 cm   |
| Unit Type of Package 2       | BB1      |
| Number of Units in Package 2 | 10       |
| Package 2 Weight             | 837.0 g  |
| Package 2 Height             | 5.5 cm   |
| Package 2 width              | 14.0 cm  |
| Package 2 Length             | 26.0 cm  |
| Unit Type of Package 3       | S01      |
| Number of Units in Package 3 | 20       |
| Package 3 Weight             | 1.684 kg |
| Package 3 Height             | 15.0 cm  |
| Package 3 width              | 15.0 cm  |
| Package 3 Length             | 40.0 cm  |

## Offer Sustainability

| Sustainable offer status   | Green Premium product   |
|----------------------------|---|
| REACh Regulation           | REACh Declaration   |
| REACh free of SVHC         | Yes   |
| EU RoHS Directive          | Compliant EU RoHS Declaration   |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| RoHS exemption information | Yes   |
| China RoHS Regulation      | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)                                    |
| Environmental Disclosure   | Product Environmental Profile   |
| Circularity Profile        | End of Life Information   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |