



New Unica - Roller blind one-way switch 6A screwless 2modules white

NU320818

Main

Range of product	New Unica
Product or component type	Shutter control
Device presentation	Mechanism
Technology type	Electromechanical
Switch function	3 positions
Number of rocker	3
Device application	Control
Colour tint	White (RAL 9003)
Type of packing	Flow-pack

Complementary	
Rated current	6 A
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50/60 Hz
Electrical durability	20000 cycles, cos phi = 0.6
Insulation resistance	> 5 MOhm at 500 V
Dielectric strength	2000 V
Minimum load breaking capacity	200 operations 1.25 In and 1.1 Un, cos phi = 0.3
Opening distance	> 3 mm
Actuator	Rocker and push-button
Number of modules	2 modules
Connections - terminals	Screwless terminals
Cable cross section	02.5 mm² rigid cable 02.5 mm² flexible cable
Material	CuZn15: terminals Thermoplastic ABS-UV stabilised: mechanism rocker PC (polycarbonate) GF10 FR: casing PBT (polybutylene terephthalate) GF30: release button
Marking	Arrow 0 position
Surface finish	Glossy

Specific treatment - integrated within the material	Untreated
Fixing mode	Clip-in
Width	45 mm
Height	45 mm
Depth	44.35 mm
Embedding depth	32.8 mm
Net weight	0.0335 kg
Ambient air temperature for operation	-540 °C
Ambient air temperature for storage	-550 °C
Standards	IEC 60669-1 LV directive
Product certifications	CE AENOR EAC NF VDE
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

Environment

IP degree of protection	IP4X
IK degree of protection	IK04
Environmental characteristic	Oil UV resistant Acetone Liquid soap Window-cleaning fluid Petrol Alcohol Bleach

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	35.0 g
Package 1 Height	4.0 cm
Package 1 width	4.5 cm
Package 1 Length	4.5 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	614.0 g
Package 2 Height	8.0 cm
Package 2 width	18.0 cm
Package 2 Length	18.5 cm
Unit Type of Package 3	S03

Number of Units in Package 3	80
Package 3 Weight	5.367 kg
Package 3 Height	30.0 cm
Package 3 width	30.0 cm
Package 3 Length	40.0 cm
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile

WEEE

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins