

Product data sheet

Specifications



Double socket outlet, New Unica, 2P +E, 16A CZ SK, white

NU206518

Main

Range	New Unica
Device application	Power supply
Product or component type	Socket-outlet
Device presentation	Complete mechanism
Socket number	2
Outlet poles configuration	2P + E
Outlet standard	Czech Republic Czech Republic
Socket additional information	Pin earth
Outlet standard description	Pin earth

Complementary

Device mounting	Flush
Rated current	16 A
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50/60 Hz
Fixing mode	2 fixing points
Colour tint	White (RAL 9003)
Connections - terminals	Screw terminals
Cable cross section	0...4 mm ² cable(s), 2 - cable stiffness: flexible 0...4 mm ² - cable stiffness: rigid
Minimum load breaking capacity	100 operations 1.25 I _n and 1.1 U _n , cos phi = 0.6
Electrical durability	10000 cycles, cos phi = 0.8
Insulation resistance	> 5 MOhm at 500 V
Dielectric strength	2000 V
Material	ASA + PC: mechanism cover ABS (acrylonitrile butadiene-styrene): cover frame
Surface finish	Glossy
Quantity per set	Set of 1 flow-pack
Standards	IEC 60884-1

Embedding depth	27 mm
Depth	35.3 mm
Width	85 mm
Height	125 mm
Net weight	0.0864 kg
Surface treatment	Untreated
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

Environment

Ambient air temperature for operation	-5...35 °C
Ambient air temperature for storage	-5...50 °C
IK degree of protection	IK01
IP degree of protection	IP21D
Environmental characteristic	Alcohol Bleach Liquid soap Acetone Window-cleaning fluid UV resistant Petrol Oil

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	86.4 g
Package 1 Height	3.8 cm
Package 1 width	8.4 cm
Package 1 Length	12.5 cm
Unit Type of Package 2	P06
Number of Units in Package 2	360
Package 2 Weight	46.448 kg
Package 2 Height	77.0 cm
Package 2 width	80.0 cm
Package 2 Length	60.0 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	5
Package 3 Weight	488.0 g
Package 3 Height	13.7 cm
Package 3 width	10.3 cm
Package 3 Length	19.3 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile